NOTES:

- 1. PRACTICE MAY BE COMBINED WITH SEDIMENT CONTROL FENCING, PER DIRECTION OF FORESTRY STAFF.
- 2. LOCATION AND LIMITS OF FENCING SHALL BE COORDINATED IN THE FIELD WITH FORESTRY STAFF.
- 3. BOUNDARIES OF PROTECTION AREA MUST BE STAKED PRIOR TO INSTALLING PROTECTIVE DEVICE.
- 4. ROOT DAMAGE SHOULD BE AVOIDED. ROOT PRUNING TO OCCUR PRIOR TO OR IN CONJUNCTION WITH INSTALLATION, AS SHOWN ON FCP PLAN OR PER DIRECTION OF FORESTRY STAFF.
- 5. PROTECTIVE SIGNAGE IS REQUIRED.
- 6. FENCING SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION. REMOVAL WITH APPROVAL BY CITY FORESTRY STAFF.

STANDARD SYMBOL

TPF — TPF —

10' MAX. BETWEEN POSTS

TREE PROTECTION AREA

NO DISTURBANCE OR ACCESS PERMITTED BEYOND THIS POINT VIOLATIONS ENFORCED PER CITY CODE CHAPTER 10.5

AREA DE PROTECCION DE ARBOLES

NINGUN DISTURBIO O ACCESO PERMITIDO MAS ALLA DE ESTA PUNTO

VIOLACIONES FORZADAS POR CODIGO CAPITULO 10.5




6' MIN. METAL 'T' FENCE POSTS DRIVEN 24" INTO THE GROUND. FENCE MIN 4' ABOVE GRADE.

NEON FLAGGING

WELDED WIRE FENCE 14/14 G.A. GALVANIZED WIRE 2"-4" OPENING

SECURE FENCING TO METAL POSTS



SIGN

APPROVED BY:

3/30/17 FORESTER

DATE:____

TREE PROTECTION FENCE DETAIL

DETAIL

A-6